

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
7 August 2003 (07.08.2003)

PCT

(10) International Publication Number  
WO 03/065775 A2

(51) International Patent Classification<sup>7</sup>:

H05K

(74) Agent: LANGER, Edward; c/o Shibolet, Yisraeli, Roberts, Zisman & Co., 44-46 Montefiore Street, 65201 Tel Aviv (IL).

(21) International Application Number: PCT/IL03/00066

(22) International Filing Date: 27 January 2003 (27.01.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

60/352,252	30 January 2002 (30.01.2002)	US
60/374,798	24 April 2002 (24.04.2002)	US
60/394,513	10 July 2002 (10.07.2002)	US

(71) Applicant and


(72) Inventor: EREL, David [IL/IL]; 8 Mordechai Street, 47441 Ramat HaSharon (IL).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI,

[Continued on next page]

(54) Title: HEAT-SINK WITH LARGE FINS-TO-AIR CONTACT AREA



(57) Abstract: A cooling device for dissipating heat to the surrounding air from at least one heat-generating component mounted on a surface, the cooling device comprising: a heat-sink having a plurality of heat-conducting sections arranged in a low-profile configuration providing large surface-to-air contact area defined by high ratio of air-passage-area to the area of the heat-conducting-sections; wherein at least one of the heat-conducting sections is in thermal contact with the heat-generating component so as to facilitate thermal flow from the heat-generating component to the air via at least one of said heat-conducting sections; wherein the heat sink is adapted to operate with air-moving means, and wherein the cooling device and the air-moving means provide reduced thermal-flow resistance from the at least one of the heat-conducting sections in contact with the heat-generating component to the air, per specific volume occupied by the cooling device.

BEST AVAILABLE COPY